



WLB 550 - Technical Specifications

Earth Mover | Bias | E-3/L-3 | TL | 5 Years

Salient Features & Benefits

Wheel Loader Bias 550, specially designed for Wheel loaders, dozers in Mining & Construction applications.

Designed to combat the harsh operating conditions:

- Special Engineered Tread pattern with cut-resistant compound
- Provides Good Traction in heavy-duty applications like construction and mining sites

Durability and Strength:

- Strong Nylon Casing.
- Heavy load-carrying capacity & Resistance to impacts.

Improved Stability:

- Large Footprint
- More ground contact area.

Less Breakdown:

- Superior Cut & Chip Tread compound
- Minimize cuts and punctures in heavy-duty loading applications



Machineries



Wheel Loader

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	17.5-25
Rec Rim	14.00/1.5
Alternate Rim	14.00/1.5DC, 14,00/1.3 DC, 13.00/1.4 DC
PR & LI/SI	16PR 158B/177A2
Section Width (mm)	445
Overall Diameter (mm)	1348
Static Load Radius (mm)	612
Rolling Circumference (mm)	4032
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	3	4.8
10	-	7300
30	-	5620
50	4250	-