

PEB 723 - Technical Specifications

Material Handling | Bias | IND-4S | TL | 5 Years

Salient Features & Benefits

Port Equipment Bias 723 tyres, specially designed for Reach Stacker in port applications.

Offers better stability and easy manoeuvring:

- Flat and Larger tread width.
- Provides Excellent grip in operation.

Suitable for heavy-duty applications:

- Robust construction.
- High load-carrying capacity.

Excellent Durability:

- Reinforced sidewalls & bead area.
- Resistance to damage.

Maximum operating efficiency:

- Specially Formulated Tread compound.
- Improved heat resistance, Quick heat dissipation and cooler running on hard concrete surfaces.

Less downtime in the Port Application:

- Deep Wide Tread Grooves
- Reduce risk of groove cracks and heat buildup in operation.



Machineries



Reach Stacker

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	18.00-25
Rec Rim	13.00/2.5
Alternate Rim	-
PR & LI/SI	40PR
Section Width (mm)	512
Overall Diameter (mm)	1675
Static Load Radius (mm)	736
Rolling Circumference (mm)	4935
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar		10.3
10		22950
25		21250