



WLB 550 - Technical Specifications

Earth Mover | Bias | E-3/L-3 | TL | 5 Years

Salient Features & Benefits

Wheel Loader Bias 550, specially designed for Wheel loaders, dozers in Mining & Construction applications.

Designed to combat the harsh operating conditions:

- Special Engineered Tread pattern with cut-resistant compound
- Provides Good Traction in heavy-duty applications like construction and mining sites

Durability and Strength:

- Strong Nylon Casing.
- Heavy load-carrying capacity & Resistance to impacts.

Improved Stability:

- Large Footprint
- More ground contact area.

Less Breakdown:

- Superior Cut & Chip Tread compound
- Minimize cuts and punctures in heavy-duty loading applications



Machineries



Wheel Loader

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	20.5-25
Rec Rim	17.00/2.0
Alternate Rim	17.00/1.7
PR & LI/SI	20PR 170B/186A2
Section Width (mm)	520
Overall Diameter (mm)	1492
Static Load Radius (mm)	672
Rolling Circumference (mm)	4463
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	3.3	4.5
10	-	9500
30	-	7320
50	6000	-