

## WLB 550 - Technical Specifications

Earth Mover | Bias | E-3/L-3 | TL | 5 Years

### Salient Features & Benefits

**Wheel Loader Bias 550, specially designed for Wheel loaders, dozers in Mining & Construction applications.**

#### Designed to combat the harsh operating conditions:

- Special Engineered Tread pattern with cut-resistant compound
- Provides Good Traction in heavy-duty applications like construction and mining sites

#### Durability and Strength:

- Strong Nylon Casing.
- Heavy load-carrying capacity & Resistance to impacts.

#### Improved Stability:

- Large Footprint
- More ground contact area.

#### Less Breakdown:

- Superior Cut & Chip Tread compound
- Minimize cuts and punctures in heavy-duty loading applications



## Machineries



Wheel Loader

**Standard:** ProductComponent.International Standards

### Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	23.5-25
Rec Rim	19.5/1.5
Alternate Rim	19.5/2.5
PR & LI/SI	20PR 117B/191A2
Section Width (mm)	597
Overall Diameter (mm)	1617
Static Load Radius (mm)	723
Rolling Circumference (mm)	4837
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	3	3.6
10	-	10900
30	-	8390
50	7300	-