

TDB 121 - Technical Specifications

Agriculture | Bias | R-1W | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 121, specially designed for tractors used in Puddling operations

Ideal for wet & moist soil

- Optimized lug design with high inner volume.
- Ensures better percolation of mud/clay or smooth operation during puddling.

Excellent Traction

- Deep tread depth with Optimized Lug Spacing.
- Provides Good lateral Traction with outstanding self-cleaning properties.

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

Extraordinary Durability

- Special Tread compound
- Ensures Longer Life and resist to cut growth.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*7536*00
Tyre Size	6-14
Rec Rim	5JA
Alternate Rim	-
PR & LI/SI	4PR 66A6/ 63A8
Section Width (mm)	155
Overall Diameter (mm)	627
Static Load Radius (mm)	290
Rolling Circumference (mm)	1875
Type	TT/TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.2	1.6	1.9
10	250	320	380	420
25	230	300	350	390
30	220	280	320	360
40	190	250	290	320
50	180	230	270	300
65	160	210	240	270