

## TDB 121 - Technical Specifications

Agriculture | Bias | R-1W | TT/TL | 5 Years



### Salient Features & Benefits

**Tractor Drive Bias 121, specially designed for tractors used in Puddling operations**

#### Ideal for wet & moist soil

- Optimized lug design with high inner volume.
- Ensures better percolation of mud/clay or smooth operation during puddling.

#### Excellent Traction

- Deep tread depth with Optimized Lug Spacing.
- Provides Good lateral Traction with outstanding self-cleaning properties.

#### Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

#### Extraordinary Durability

- Special Tread compound
- Ensures Longer Life and resist to cut growth.

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/19*7540*00
Tyre Size	8.3-20
Rec Rim	W7
Alternate Rim	-
PR & LI/SI	8PR 101A6/ 98A8
Section Width (mm)	211
Overall Diameter (mm)	892
Static Load Radius (mm)	412
Rolling Circumference (mm)	2668
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	2	2.4	2.8	3.2
10	870	970	1060	1160
25	810	900	990	1070
30	740	830	910	990
40	660	740	810	880
50	620	690	760	825
65	560	620	680	740