



TDR 850 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Tractor Drive Radial 850 specially designed for soil tillage and both field and road transport.

Soil Protection

- Wider and Longer Footprint.
- low soil compaction and excellent load distribution that avoids damage to crops.

Exceptional Traction

- Optimized Tread design.
- Ensuring excellent grip and reducing the risk of slippage.

Outstanding Self Cleaning Properties

- Unique Mud Breaker
- Allow for a quick change from field operations to road usage.

Higher Load Capacity

- Reinforced Construction.
- Withstand high load carrying in operation.

Superior Roadability

- Higher angle lug and lug overlap at the center of the tread.
- Smooth driving experience.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*7814*00
Tyre Size	250/85R20 (9.5R20)
Rec Rim	W8
Alternate Rim	-
PR & LI/SI	116 D
Section Width (mm)	251
Overall Diameter (mm)	934
Static Load Radius (mm)	430
Rolling Circumference (mm)	2805
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.2	1.6	2	2.4
Static	1380	1770	2160	2550	2880

Mixed Application

km/h / bar	0.8	1.2	1.6	2	2.4
10	900	1160	1410	1670	1880
25	670	850	1040	1230	1390
30	640	820	1010	1190	1340
40	600	770	940	1110	1250
50	600	770	940	1110	1250