



TDR 850 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Tractor Drive Radial 850 specially designed for soil tillage and both field and road transport.

Soil Protection

- Wider and Longer Footprint.
- low soil compaction and excellent load distribution that avoids damage to crops.

Exceptional Traction

- Optimized Tread design.
- Ensuring excellent grip and reducing the risk of slippage.

Outstanding Self Cleaning Properties

- Unique Mud Breaker
- Allow for a quick change from field operations to road usage.

Higher Load Capacity

- Reinforced Construction.
- Withstand high load carrying in operation.

Superior Roadability

- Higher angle lug and lug overlap at the center of the tread.
- Smooth driving experience.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7249*00
Tyre Size	280/85R20 (11.2R20)
Rec Rim	W10
Alternate Rim	-
PR & LI/SI	116 D
Section Width (mm)	292
Overall Diameter (mm)	984
Static Load Radius (mm)	450
Rolling Circumference (mm)	2943
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	1	1.2	1.4	1.6	1.9
Static	1860	2090	2320	2580	2880

Mixed Application

km/h / bar	1	1.2	1.4	1.6	1.9
10	1220	1370	1520	1680	1880
25	960	1080	1200	1330	1480
30	930	1050	1160	1290	1440
40	890	1000	1110	1230	1370
50	850	960	1060	1180	1310
65	810	910	1010	1120	1250