



TDR 850 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Tractor Drive Radial 850 specially designed for soil tillage and both field and road transport.

Soil Protection

- Wider and Longer Footprint.
- low soil compaction and excellent load distribution that avoids damage to crops.

Exceptional Traction

- Optimized Tread design.
- Ensuring excellent grip and reducing the risk of slippage.

Outstanding Self Cleaning Properties

- Unique Mud Breaker
- Allow for a quick change from field operations to road usage.

Higher Load Capacity

- Reinforced Construction.
- Withstand high load carrying in operation.

Superior Roadability

- Higher angle lug and lug overlap at the center of the tread.
- Smooth driving experience.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6653*00
Tyre Size	280/85R24 (11.2R24)
Rec Rim	W10
Alternate Rim	W9, DW10
PR & LI/SI	115 D
Section Width (mm)	292
Overall Diameter (mm)	1086
Static Load Radius (mm)	502
Rolling Circumference (mm)	3248
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1	1.2	1.4	1.6
Static	1770	2020	2280	2530	2790

Mixed Application

km/h / bar	0.8	1	1.2	1.4	1.6
10	1160	1320	1490	1650	1820
25	910	1040	1170	1300	1440
30	890	1010	1140	1270	1400
40	840	960	1080	1200	1330
50	810	920	1040	1160	1280
65	770	880	990	1100	1215