



TDR 850 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Tractor Drive Radial 850 specially designed for soil tillage and both field and road transport.

Soil Protection

- Wider and Longer Footprint.
- low soil compaction and excellent load distribution that avoids damage to crops.

Exceptional Traction

- Optimized Tread design.
- Ensuring excellent grip and reducing the risk of slippage.

Outstanding Self Cleaning Properties

- Unique Mud Breaker
- Allow for a quick change from field operations to road usage.

Higher Load Capacity

- Reinforced Construction.
- Withstand high load carrying in operation.

Superior Roadability

- Higher angle lug and lug overlap at the center of the tread.
- Smooth driving experience.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6654*00
Tyre Size	320/85R24 (12.4R24)
Rec Rim	W11
Alternate Rim	W9, W10, DW11
PR & LI/SI	122 D
Section Width (mm)	329
Overall Diameter (mm)	1154
Static Load Radius (mm)	530
Rolling Circumference (mm)	3452
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1	1.2	1.4	1.6
Static	2190	2480	2810	3130	3450

Mixed Application

km/h / bar	0.8	1	1.2	1.4	1.6
10	1430	1620	1830	2040	2250
25	1130	1280	1450	1610	1780
30	1090	1240	1400	1560	1730
40	1040	1180	1340	1490	1640
50	1000	1130	1280	1430	1580
65	950	1080	1220	1360	1500