



TDR 850 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Tractor Drive Radial 850 specially designed for soil tillage and both field and road transport.

Soil Protection

- Wider and Longer Footprint.
- low soil compaction and excellent load distribution that avoids damage to crops.

Exceptional Traction

- Optimized Tread design.
- Ensuring excellent grip and reducing the risk of slippage.

Outstanding Self Cleaning Properties

- Unique Mud Breaker
- Allow for a quick change from field operations to road usage.

Higher Load Capacity

- Reinforced Construction.
- Withstand high load carrying in operation.

Superior Roadability

- Higher angle lug and lug overlap at the center of the tread.
- Smooth driving experience.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6655*00
Tyre Size	340/85R24 (13.6R24)
Rec Rim	W12
Alternate Rim	W11
PR & LI/SI	125 D
Section Width (mm)	353
Overall Diameter (mm)	1188
Static Load Radius (mm)	544
Rolling Circumference (mm)	3554
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1	1.2	1.4	1.6
Static	2420	2760	3110	3450	3800

Mixed Application

km/h / bar	0.8	1	1.2	1.4	1.6
10	1580	1800	2030	2250	2480
25	1240	1420	1600	1780	1960
30	1210	1380	1550	1730	1900
40	1150	1310	1480	1640	1810
50	1100	1260	1420	1580	1730
65	1050	1200	1350	1500	1650