



HRR 200 - Technical Specifications

Agriculture | Radial | R-1 | TL | 7 Years

Salient Features & Benefits

HRR 200 High-performance radial tyre for harvesters. Designed for superior field grip, stubble resistance, and soil care.

High Traction & Self-Cleaning

- Optimized lug design with unique dual mud breaker.
- Delivers excellent grip in wet or tilled fields and sheds mud for uninterrupted operations

Low Soil Compaction

- Wider footprint with uniform pressure distribution
- Protects soil structure during harvesting, improving productivity and reducing rutting in operation.

Stubble & Puncture Resistance

- Special Stubble-Resistant (SSR) compound
- Defends against sharp stubble damage and improves overall tyre durability

Operational Stability

- Reinforced construction with steel-belted casing.
- Maintains stability and control even on uneven, soft, or hilly terrain & protect against punctures



Machineries



Harvester

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	620/75R26 (SB)
Rec Rim	DW20B
Alternate Rim	-
PR & LI/SI	167 AB
Section Width (mm)	625
Overall Diameter (mm)	1590
Static Load Radius (mm)	714
Rolling Circumference (mm)	4755
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Harvester Application

km/h / bar	1.6	2	2.4	2.8	3.2
10	5850	6420	6840	7490	8180
15	5230	5740	6110	6690	7300
25	4630	5080	5420	5930	6470
30	4170	4580	4880	5340	5830
40	3900	4280	4560	4990	5450

High Torque

km/h / bar	1.6	2	2.4	2.8	3.2
10	4170	4580	4880	5340	5830

Cyclic Application

km/h / bar	4
10	9270