

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*8980*00
Tyre Size	VF 600/60R28 NRO (SB)
Rec Rim	DW20B
Alternate Rim	DW21B
NRO	DW18L
PR & LI/SI	160 D
Section Width (mm)	597
Overall Diameter (mm)	1431
Static Load Radius (mm)	653
Rolling Circumference (mm)	4297
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	2460	2870	3290	3700	4520	4950
25	2310	2690	3080	3460	4230	4640
30	2280	2660	3050	3430	4190	4590
40	2240	2610	2990	3360	4110	4500
50	2240	2610	2990	3360	4110	4500
65	2240	2610	2990	3360	4110	4500
70	2060	2390	2740	3080	3770	4130