

XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.

Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

Prevent lug shuffling in operation

- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	600/65R28 (HD)
Rec Rim	DW20B
Alternate Rim	W18L
PR & LI/SI	154D
Section Width (mm)	611
Overall Diameter (mm)	1491
Static Load Radius (mm)	677
Rolling Circumference (mm)	4459
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	1.2	1.6	1.8	2	2.4
Static	6120	7250	7660	8050	8630

Mixed Application

km/h / bar	1.2	1.6	1.8	2	2.4
10	3990	4730	5000	5250	5630
25	3150	3730	3950	4150	4440
30	3060	3620	3830	4030	4310
40	2910	3450	3650	3830	4110
50	2790	3310	3500	3680	3940
65	2660	3150	3330	3500	3750