

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Tractor

Harvester

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*9036*00
Tyre Size	VF 600/65R28 CFO (SB)
Rec Rim	DW21B
Alternate Rim	DW20B
PR & LI/SI	166 AB
Section Width (mm)	597
Overall Diameter (mm)	1491
Static Load Radius (mm)	677
Rolling Circumference (mm)	4477
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

CFO

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4
Upto 15 Cyc.	3360	3920	4490	4890	5980	6640	7180
Upto 30 Cyc.	2810	3280	3760	4100	5010	5560	6020

Harvester Application

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4
10	2730	3180	3640	3970	4850	5390	5830
25	2550	2980	3410	3720	4540	5050	5460
30	2530	2950	3380	3680	4500	5000	5410
40	2480	2890	3310	3610	4410	4900	5300
50	2280	2650	3040	3310	4050	4500	4860