

XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.

Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

Prevent lug shuffling in operation

- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	600/70R28 (HD)
Rec Rim	DW20B
Alternate Rim	DW18L, W18L
PR & LI/SI	161D
Section Width (mm)	611
Overall Diameter (mm)	1551
Static Load Radius (mm)	702
Rolling Circumference (mm)	4639
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.6	2	2.4	2.8
Static	5240	8230	9020	9610	10640

Mixed Application

km/h / bar	0.8	1.6	2	2.4	2.8
10	3420	5370	5880	6270	6940
25	2700	4240	4650	4950	5480
30	2620	4120	4510	4810	5320
40	2500	3920	4290	4580	5060
50	2390	3760	4120	4390	4860
65	2280	3580	3920	4180	4625