

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*9037*00
Tyre Size	VF 540/65R30 CFO (SB)
Rec Rim	DW20B
Alternate Rim	W18L,DW18L
PR & LI/SI	161 AB
Section Width (mm)	539
Overall Diameter (mm)	1464
Static Load Radius (mm)	671
Rolling Circumference (mm)	4396
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

CFO

km/h / bar	0.6	0.8	1	1.2	1.6	2.4
Upto 15 Cyc.	3020	3540	4040	4540	6180	6270
Upto 30 Cyc.	2530	2960	3380	3800	5180	5250

Harvester Application

km/h / bar	0.6	0.8	1	1.2	1.6	2.4
10	2450	2870	3280	3690	5020	5090
25	2300	2690	3070	3450	4700	4760
30	2270	2660	3040	3420	4650	4720
40	2230	2610	2980	3350	4560	4625
50	2050	2390	2730	3070	4180	4240