

## VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

### Salient Features & Benefits

### VF Drive Radial 2000, specially designed Ultra Modern Tractor.

#### Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

#### Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

#### Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

#### Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

#### Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

#### Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

#### NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



## Machineries



**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*8771*00
Tyre Size	VF 600/60R30 NRO (SB)
Rec Rim	DW20B
Alternate Rim	DW21B
NRO	DW18L
PR & LI/SI	162 D
Section Width (mm)	597
Overall Diameter (mm)	1482
Static Load Radius (mm)	678
Rolling Circumference (mm)	4450
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	2540	2970	3390	3820	4660	5230
25	2380	2780	3170	3570	4370	4890
30	2360	2750	3140	3540	4320	4850
40	2310	2700	3080	3470	4240	4750
50	2310	2700	3080	3470	4240	4750
65	2310	2700	3080	3470	4240	4750
70	2120	2480	2830	3180	3890	4360