

XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.

Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

Prevent lug shuffling in operation

- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	600/70R30 (HD)
Rec Rim	DW20B
Alternate Rim	DW18L,W18L
PR & LI/SI	152 D
Section Width (mm)	611
Overall Diameter (mm)	1602
Static Load Radius (mm)	728
Rolling Circumference (mm)	4791
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1	1.2	1.4	1.6
Static	5220	5960	6690	7430	8170

Mixed Application

km/h / bar	0.8	1	1.2	1.4	1.6
10	3410	3890	4370	4850	5330
25	2690	3070	3450	3830	4210
30	2610	2980	3350	3710	4080
40	2490	2840	3190	3540	3890
50	2380	2720	3060	3390	3730
65	2270	2590	2910	3230	3550
70	-	-	-	-	-