

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/21*10882*00
Tyre Size	VF 710/55R30 NRO (SB)
Rec Rim	DW25B
Alternate Rim	-
NRO	DW23B,DW24B
PR & LI/SI	165 D
Section Width (mm)	708
Overall Diameter (mm)	1544
Static Load Radius (mm)	704
Rolling Circumference (mm)	4636
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6
10	3060	3580	4080	4590	5670
25	2860	3350	3820	4300	5300
30	2840	3320	3780	4250	5250
40	2780	3250	3710	4170	5150
50	2780	3250	3710	4170	5150
65	2780	3250	3710	4170	5150
70	2550	2980	3400	3830	4720