



TDR 850 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Tractor Drive Radial 850 specially designed for soil tillage and both field and road transport.

Soil Protection

- Wider and Longer Footprint.
- low soil compaction and excellent load distribution that avoids damage to crops.

Exceptional Traction

- Optimized Tread design.
- Ensuring excellent grip and reducing the risk of slippage.

Outstanding Self Cleaning Properties

- Unique Mud Breaker
- Allow for a quick change from field operations to road usage.

Higher Load Capacity

- Reinforced Construction.
- Withstand high load carrying in operation.

Superior Roadability

- Higher angle lug and lug overlap at the center of the tread.
- Smooth driving experience.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6665*00
Tyre Size	320/85R32 (12.4R32)
Rec Rim	W11
Alternate Rim	W9, W10, DW11
PR & LI/SI	126 D
Section Width (mm)	329
Overall Diameter (mm)	1357
Static Load Radius (mm)	631
Rolling Circumference (mm)	4075
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1	1.2	1.4	1.6
Static	2510	2850	3220	3570	3910

Mixed Application

km/h / bar	0.8	1	1.2	1.4	1.6
10	1640	1860	2100	2330	2550
25	1290	1470	1660	1840	2010
30	1250	1430	1610	1780	1960
40	1190	1360	1530	1700	1860
50	1140	1300	1470	1630	1790
65	1090	1240	1400	1550	1700