



HRR 200 - Technical Specifications

Agriculture | Radial | R-1 | TL | 7 Years

Salient Features & Benefits

HRR 200 High-performance radial tyre for harvesters. Designed for superior field grip, stubble resistance, and soil care.

High Traction & Self-Cleaning

- Optimized lug design with unique dual mud breaker.
- Delivers excellent grip in wet or tilled fields and sheds mud for uninterrupted operations

Low Soil Compaction

- Wider footprint with uniform pressure distribution
- Protects soil structure during harvesting, improving productivity and reducing rutting in operation.

Stubble & Puncture Resistance

- Special Stubble-Resistant (SSR) compound
- Defends against sharp stubble damage and improves overall tyre durability

Operational Stability

- Reinforced construction with steel-belted casing.
- Maintains stability and control even on uneven, soft, or hilly terrain & protect against punctures



Machineries



Harvester

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	650/75R32 (SB)
Rec Rim	DW21B
Alternate Rim	DW20B, DW23B
PR & LI/SI	172 AB
Section Width (mm)	655
Overall Diameter (mm)	1789
Static Load Radius (mm)	809
Rolling Circumference (mm)	5351
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Harvester Application

km/h / bar	1.6	2	2.4	2.8	3.2
10	6870	7530	8030	8790	9450
15	6140	6730	7170	7850	8440
25	5440	5960	6350	6960	7480
30	4900	5370	5720	6270	6740
40	4580	5020	5350	5860	6300

High Torque

km/h / bar	1.6	2	2.4	2.8	3.2
10	4900	5370	5720	6270	6740

Cyclic Application

km/h / bar	4
10	10710