



## HRR 200 - Technical Specifications

Agriculture | Radial | R-1 | TL | 7 Years

### Salient Features & Benefits

**HRR 200 High-performance radial tyre for harvesters. Designed for superior field grip, stubble resistance, and soil care.**

#### High Traction & Self-Cleaning

- Optimized lug design with unique dual mud breaker.
- Delivers excellent grip in wet or tilled fields and sheds mud for uninterrupted operations

#### Low Soil Compaction

- Wider footprint with uniform pressure distribution
- Protects soil structure during harvesting, improving productivity and reducing rutting in operation.

#### Stubble & Puncture Resistance

- Special Stubble-Resistant (SSR) compound
- Defends against sharp stubble damage and improves overall tyre durability

#### Operational Stability

- Reinforced construction with steel-belted casing.
- Maintains stability and control even on uneven, soft, or hilly terrain & protect against punctures



## Machineries



Harvester

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	800/65R32 (SB)
Rec Rim	DW27B
Alternate Rim	DW25B, DH27B
PR & LI/SI	181 AB
Section Width (mm)	818
Overall Diameter (mm)	1853
Static Load Radius (mm)	835
Rolling Circumference (mm)	5542
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Harvester Application

km/h / bar	2	2.4	2.8	3.2	3.6
10	8750	9450	10340	11150	12380
15	7810	8440	9230	9960	11060
25	6930	7480	8180	8820	9800
30	6240	6740	7370	7950	8830
40	5830	6300	6890	7430	8250

### High Torque

km/h / bar	2	2.4	2.8	3.2	3.6
10	6240	6740	7370	7950	8830

### Cyclic Application

km/h / bar	5
10	14030