



## HRR 200 - Technical Specifications

Agriculture | Radial | R-1 | TL | 7 Years

### Salient Features & Benefits

**HRR 200 High-performance radial tyre for harvesters. Designed for superior field grip, stubble resistance, and soil care.**

#### High Traction & Self-Cleaning

- Optimized lug design with unique dual mud breaker.
- Delivers excellent grip in wet or tilled fields and sheds mud for uninterrupted operations

#### Low Soil Compaction

- Wider footprint with uniform pressure distribution
- Protects soil structure during harvesting, improving productivity and reducing rutting in operation.

#### Stubble & Puncture Resistance

- Special Stubble-Resistant (SSR) compound
- Defends against sharp stubble damage and improves overall tyre durability

#### Operational Stability

- Reinforced construction with steel-belted casing.
- Maintains stability and control even on uneven, soft, or hilly terrain & protect against punctures



## Machineries



Harvester

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	900/60R32 (SB)
Rec Rim	DW28B
Alternate Rim	DW27B, DW30B
PR & LI/SI	191 D
Section Width (mm)	896
Overall Diameter (mm)	1893
Static Load Radius (mm)	852
Rolling Circumference (mm)	5662
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Harvester Application

km/h / bar	2.8	3.2	3.6	4	4.4
10	11580	12480	13290	14000	16350
15	10340	11150	11870	12500	14610
25	9150	9860	10500	11060	12920
30	8880	9570	10190	10730	12540
40	8450	9110	9700	10220	11940
65	7720	8320	8860	9330	10900

### High Torque

km/h / bar	2.8	3.2	3.6	4	4.4
10	8880	9570	10190	10730	12540

### Cyclic Application

km/h / bar	5.5
10	18530