

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10236*00
Tyre Size	VF 380/85R34 (SB)
Rec Rim	W13
Alternate Rim	W12,DW12,DW13
NRO	-
PR & LI/SI	149 D
Section Width (mm)	383
Overall Diameter (mm)	1510
Static Load Radius (mm)	698
Rolling Circumference (mm)	4516
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
10	1940	2260	2570	2890	3220	3580
25	1810	2110	2410	2710	3020	3350
30	1800	2090	2390	2680	2990	3320
40	1760	2050	2340	2630	2930	3250
50	1760	2050	2340	2630	2930	3250
65	1760	2050	2340	2630	2930	3250
70	1610	1880	2150	2410	2690	2980