

## VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

### Salient Features & Benefits

### VF Drive Radial 2000, specially designed Ultra Modern Tractor.

#### Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

#### Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

#### Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

#### Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

#### Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

#### Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

#### NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



## Machineries



**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*10233*00
Tyre Size	VF 600/60R34 (SB)
Rec Rim	DW20B
Alternate Rim	DW21B
NRO	-
PR & LI/SI	160 D
Section Width (mm)	597
Overall Diameter (mm)	1584
Static Load Radius (mm)	729
Rolling Circumference (mm)	4757
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
10	2700	3150	3600	4040	4490	4950
25	2520	2950	3370	3780	4200	4640
30	2500	2920	3340	3740	4160	4590
40	2450	2860	3270	3670	4080	4500
50	2450	2860	3270	3670	4080	4500
65	2450	2860	3270	3670	4080	4500
70	2250	2620	3000	3370	3740	4130