

## VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

### Salient Features & Benefits

### VF Drive Radial 2000, specially designed Ultra Modern Tractor.

#### Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

#### Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

#### Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

#### Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

#### Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

#### Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

#### NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



## Machineries



**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*10232*00
Tyre Size	VF 650/60R34 NRO (SB)
Rec Rim	DW23B
Alternate Rim	DW21B
NRO	DW20B
PR & LI/SI	168 D
Section Width (mm)	650
Overall Diameter (mm)	1644
Static Load Radius (mm)	731
Rolling Circumference (mm)	4937
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	3050	3550	4060	4570	5590	6160
25	2850	3330	3800	4270	5230	5770
30	2830	3290	3760	4230	5180	5710
40	2770	3230	3690	4150	5080	5600
50	2770	3230	3690	4150	5080	5600
65	2770	3230	3690	4150	5080	5600
70	2540	2960	3390	3810	4660	5140