

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

| | |
|----------------------------|------------------------|
| ECE | E11*106R00/20*10238*00 |
| Tyre Size | VF 650/65R34 NRO (SB) |
| Rec Rim | DW23B |
| Alternate Rim | DW21B |
| NRO | DW20B |
| PR & LI/SI | 170 D |
| Section Width (mm) | 650 |
| Overall Diameter (mm) | 1710 |
| Static Load Radius (mm) | 781 |
| Rolling Circumference (mm) | 5135 |
| Type | TL |

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

| km/h / bar | 0.6 | 0.8 | 1 | 1.2 | 1.6 | 2 |
|------------|------|------|------|------|------|------|
| 10 | 3380 | 3940 | 4500 | 5060 | 6000 | 6600 |
| 25 | 3160 | 3690 | 4210 | 4740 | 5610 | 6180 |
| 30 | 3130 | 3650 | 4170 | 4690 | 5560 | 6120 |
| 40 | 3070 | 3580 | 4090 | 4600 | 5450 | 6000 |
| 50 | 3070 | 3580 | 4090 | 4600 | 5450 | 6000 |
| 65 | 3070 | 3580 | 4090 | 4600 | 5450 | 6000 |
| 70 | 2820 | 3280 | 3750 | 4220 | 5000 | 5500 |