

XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.

Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

Prevent lug shuffling in operation

- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7432*00
Tyre Size	600/70R34
Rec Rim	DW20B
Alternate Rim	-
PR & LI/SI	160 D
Section Width (mm)	611
Overall Diameter (mm)	1704
Static Load Radius (mm)	778
Rolling Circumference (mm)	5096
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	1.2	1.6	1.8	2	2.4
Static	7310	8950	9430	9820	10350

Mixed Application

km/h / bar	1.2	1.6	1.8	2	2.4
10	4770	5840	6150	6410	6750
25	3770	4610	4860	5060	5330
30	3660	4470	4720	4910	5180
40	3480	4260	4490	4680	4930
50	3340	4080	4310	4480	4730
65	3180	3890	4100	4270	4500