

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10240*00
Tyre Size	VF 600/70R34 NRO (SB)
Rec Rim	DW21B
Alternate Rim	DW20B
NRO	DW20B
PR & LI/SI	170 D
Section Width (mm)	603
Overall Diameter (mm)	1704
Static Load Radius (mm)	778
Rolling Circumference (mm)	5117
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	3270	3820	4360	4910	6000	6600
25	3060	3570	4080	4590	5610	6180
30	3030	3540	4040	4550	5560	6120
40	2970	3470	3960	4460	5450	6000
50	2970	3470	3960	4460	5450	6000
65	2970	3470	3960	4460	5450	6000
70	2720	3180	3630	4090	5000	5500