

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Tractor



Harvester

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10234*00
Tyre Size	VF 710/60R34 NRO (SB)
Rec Rim	DW25B
Alternate Rim	DW24B,DW27B
NRO	DW23B
PR & LI/SI	173 D
Section Width (mm)	708
Overall Diameter (mm)	1716
Static Load Radius (mm)	783
Rolling Circumference (mm)	5153
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1	1.2	1.4	1.6	2
10	4070	4650	5240	5820	6400	7150
25	3810	4360	4900	5450	5990	6700
30	3770	4310	4860	5400	5940	6630
40	3700	4230	4760	5290	5820	6500
50	3700	4230	4760	5290	5820	6500
65	3700	4230	4760	5290	5820	6500
70	3390	3880	4370	4850	5340	5960