



TDR 850 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Tractor Drive Radial 850 specially designed for soil tillage and both field and road transport.

Soil Protection

- Wider and Longer Footprint.
- low soil compaction and excellent load distribution that avoids damage to crops.

Exceptional Traction

- Optimized Tread design.
- Ensuring excellent grip and reducing the risk of slippage.

Outstanding Self Cleaning Properties

- Unique Mud Breaker
- Allow for a quick change from field operations to road usage.

Higher Load Capacity

- Reinforced Construction.
- Withstand high load carrying in operation.

Superior Roadability

- Higher angle lug and lug overlap at the center of the tread.
- Smooth driving experience.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	320/85R36 (12.4R36)
Rec Rim	W11
Alternate Rim	-
PR & LI/SI	148 D
Section Width (mm)	329
Overall Diameter (mm)	1458
Static Load Radius (mm)	682
Rolling Circumference (mm)	4361
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2.4	3	3.4	3.8	4.6
Static	4880	5570	5960	6330	7250

Mixed Application

km/h / bar	2.4	3	3.4	3.8	4.6
10	3180	3630	3890	4130	4730
25	2510	2870	3070	3260	3730
30	2440	2780	2980	3160	3620
40	2320	2650	2840	3010	3450
50	2230	2540	2720	2890	3310
65	2120	2420	2590	2750	3150