



TDR 850 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Tractor Drive Radial 850 specially designed for soil tillage and both field and road transport.

Soil Protection

- Wider and Longer Footprint.
- low soil compaction and excellent load distribution that avoids damage to crops.

Exceptional Traction

- Optimized Tread design.
- Ensuring excellent grip and reducing the risk of slippage.

Outstanding Self Cleaning Properties

- Unique Mud Breaker
- Allow for a quick change from field operations to road usage.

Higher Load Capacity

- Reinforced Construction.
- Withstand high load carrying in operation.

Superior Roadability

- Higher angle lug and lug overlap at the center of the tread.
- Smooth driving experience.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6669*00
Tyre Size	340/85R36 (13.6R36)
Rec Rim	W12
Alternate Rim	W11
PR & LI/SI	132 D
Section Width (mm)	353
Overall Diameter (mm)	1492
Static Load Radius (mm)	696
Rolling Circumference (mm)	4463
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1	1.2	1.4	1.6
Static	2940	3360	3770	4190	4600

Mixed Application

km/h / bar	0.8	1	1.2	1.4	1.6
10	1920	2190	2460	2730	3000
25	1520	1730	1940	2160	2370
30	1470	1680	1890	2090	2300
40	1400	1600	1800	1990	2190
50	1340	1530	1720	1910	2100
65	1280	1460	1640	1820	2000