

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10237*00
Tyre Size	VF 420/85R38 (SB)
Rec Rim	DW15L
Alternate Rim	DW14L
NRO	-
PR & LI/SI	155 D
Section Width (mm)	429
Overall Diameter (mm)	1679
Static Load Radius (mm)	777
Rolling Circumference (mm)	5022
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
10	2350	2750	3150	3540	3930	4260
25	2200	2580	2950	3320	3680	3990
30	2180	2550	2920	3280	3640	3950
40	2140	2500	2860	3220	3570	3875
50	2140	2500	2860	3220	3570	3875
65	2140	2500	2860	3220	3570	3875
70	1960	2290	2620	2950	3280	3560