

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/21*10879*00
Tyre Size	VF 650/60R38 NRO (SB)
Rec Rim	DW23B
Alternate Rim	DW21B
NRO	DW20B
PR & LI/SI	173 D
Section Width (mm)	650
Overall Diameter (mm)	1745
Static Load Radius (mm)	804
Rolling Circumference (mm)	5240
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4
10	3210	3740	4280	4810	5890	6520	7150
25	3010	3500	4010	4500	5510	6110	6700
30	2980	3470	3970	4460	5460	6050	6630
40	2920	3400	3890	4370	5350	5930	6500
50	2920	3400	3890	4370	5350	5930	6500
65	2920	3400	3890	4370	5350	5930	6500
70	2680	3120	3570	4010	4910	5440	5960