

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Tractor

Harvester

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*9035*00
Tyre Size	VF 650/65R38 NRO (SB)
Rec Rim	DW23B
Alternate Rim	DW21B
NRO	DW20B
PR & LI/SI	180 D
Section Width (mm)	650
Overall Diameter (mm)	1811
Static Load Radius (mm)	831
Rolling Circumference (mm)	5438
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4	2.8	3.2
10	3540	4140	4730	5160	6300	7010	7560	8270	8800
25	3320	3870	4430	4830	5900	6560	7080	7750	8240
30	3280	3840	4390	4780	5840	6500	7010	7670	8160
40	3220	3760	4300	4690	5730	6370	6870	7520	8000
50	3220	3760	4300	4690	5730	6370	6870	7520	8000
65	3220	3760	4300	4690	5730	6370	6870	7520	8000
70	2950	3450	3940	4300	5260	5840	6300	6900	7340