

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*8675*00
Tyre Size	VF 710/60R38 NRO (SB)
Rec Rim	DW25B
Alternate Rim	DW24B,DW27B
NRO	DW23B
PR & LI/SI	174 D
Section Width (mm)	708
Overall Diameter (mm)	1817
Static Load Radius (mm)	834
Rolling Circumference (mm)	5456
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	3670	4280	4900	5510	6730	7370
25	3440	4010	4580	5160	6300	6900
30	3410	3970	4540	5110	6240	6830
40	3340	3890	4450	5010	6120	6700
50	3340	3890	4450	5010	6120	6700
65	3340	3890	4450	5010	6120	6700
70	3060	3570	4080	4600	5610	6150