

XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.

Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

Prevent lug shuffling in operation

- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*8770*00
Tyre Size	650/75R38
Rec Rim	DW21B
Alternate Rim	-
PR & LI/SI	169D
Section Width (mm)	655
Overall Diameter (mm)	1941
Static Load Radius (mm)	885
Rolling Circumference (mm)	5805
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.2	1.6	2	2.4
Static	7200	9270	11340	12440	13340

Mixed Application

km/h / bar	0.8	1.2	1.6	2	2.4
10	4700	6050	7400	8120	8700
25	3710	4780	5840	6410	6870
30	3600	4630	5670	6220	6670
40	3430	4410	5400	5920	6350
50	3290	4230	5180	5680	6090
65	3130	4030	4930	5410	5800