

XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.

Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

Prevent lug shuffling in operation

- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*6965*00
Tyre Size	650/85R38
Rec Rim	DW23B
Alternate Rim	DW20B, DW21B
PR & LI/SI	173D
Section Width (mm)	675
Overall Diameter (mm)	2071
Static Load Radius (mm)	939
Rolling Circumference (mm)	6194
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.2	1.6	2	2.4
Static	8070	10370	12670	13920	14950

Mixed Application

km/h / bar	0.8	1.2	1.6	2	2.4
10	5270	6770	8270	9080	9750
25	4160	5340	6530	7170	7700
30	4040	5190	6340	6960	7480
40	3840	4940	6030	6620	7120
50	3690	4740	5790	6350	6830
65	3510	4510	5510	6050	6500