

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10241*00
Tyre Size	VF 650/85R38 (SB)
Rec Rim	DW23B
Alternate Rim	DW20B,DW23B
NRO	-
PR & LI/SI	182 D
Section Width (mm)	663
Overall Diameter (mm)	2071
Static Load Radius (mm)	939
Rolling Circumference (mm)	6194
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	4630	5400	6170	6950	8490	9350
25	4340	5060	5780	6510	7950	8760
30	4290	5010	5720	6450	7870	8670
40	4210	4910	5610	6320	7720	8500
50	4210	4910	5610	6320	7720	8500
65	4210	4910	5610	6320	7720	8500
70	3860	4500	5150	5800	7080	7800