

## XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

### Salient Features & Benefits

**Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.**

#### Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

#### Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

#### Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

#### Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

#### Prevent lug shuffling in operation

- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

#### Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/19*6971*00
Tyre Size	710/70R38
Rec Rim	DW23B
Alternate Rim	DW25B
PR & LI/SI	178D
Section Width (mm)	716
Overall Diameter (mm)	1959
Static Load Radius (mm)	893
Rolling Circumference (mm)	5854
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	1.6	1.8	2	2.4	2.8	3.2	3.4
Static	12210	12860	13410	14280	15640	16880	17250

### Mixed Application

km/h / bar	1.6	1.8	2	2.4	2.8	3.2	3.4
10	7970	8390	8750	9320	10200	11010	11250
25	6290	6620	6910	7360	8060	8700	8890
30	6110	6430	6700	7140	7820	8440	8630
40	5810	6120	6380	6800	7450	8040	8210
50	5580	5870	6120	6520	7140	7710	7880
65	5310	5590	5830	6210	6800	7340	7500