

## VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

### Salient Features & Benefits

### VF Drive Radial 2000, specially designed Ultra Modern Tractor.

#### Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

#### Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

#### Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

#### Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

#### Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

#### Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

#### NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



## Machineries



**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*9027*00
Tyre Size	VF 710/70R38 NRO (SB)
Rec Rim	DW25B
Alternate Rim	DW24B,DW23B
NRO	DW23B
PR & LI/SI	181 D
Section Width (mm)	705
Overall Diameter (mm)	1959
Static Load Radius (mm)	893
Rolling Circumference (mm)	5883
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	4280	4990	5700	6410	7840	9080
25	4010	4680	5340	6000	7340	8500
30	3970	4630	5280	5950	7270	8420
40	3890	4540	5180	5830	7130	8250
50	3890	4540	5180	5830	7130	8250
65	3890	4540	5180	5830	7130	8250
70	3570	4170	4750	5350	6540	7570