

## VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

### Salient Features & Benefits

### VF Drive Radial 2000, specially designed Ultra Modern Tractor.

#### Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

#### Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

#### Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

#### Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

#### Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

#### Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

#### NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



## Machineries



Tractor



Harvester

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*8769*00
Tyre Size	VF 800/70R38 NRO (SB)
Rec Rim	DW28B
Alternate Rim	DW25B, DW27B, DW30B
NRO	DW27B
PR & LI/SI	187 D
Section Width (mm)	804
Overall Diameter (mm)	2085
Static Load Radius (mm)	945
Rolling Circumference (mm)	6261
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	5380	6280	7170	8070	9870	10730
25	5040	5880	6720	7560	9240	10040
30	4990	5820	6650	7490	9150	9950
40	4890	5710	6520	7340	8970	9750
50	4890	5710	6520	7340	8970	9750
65	4890	5710	6520	7340	8970	9750
70	4490	5240	5980	6730	8230	8940