

XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.

Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

Prevent lug shuffling in operation


- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*6970*00
Tyre Size	620/70R42
Rec Rim	DW20B
Alternate Rim	DW18L, W18L
PR & LI/SI	166D
Section Width (mm)	625
Overall Diameter (mm)	1935
Static Load Radius (mm)	892
Rolling Circumference (mm)	5787
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.2	1.6	2	2.4
Static	6600	8490	10370	11390	12190

Mixed Application

km/h / bar	0.8	1.2	1.6	2	2.4
10	4310	5540	6770	7430	7950
25	3400	4370	5340	5870	6280
30	3300	4240	5190	5690	6100
40	3140	4040	4940	5420	5800
50	3010	3870	4740	5200	5570
65	2870	3690	4510	4950	5300