

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Tractor



Harvester

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*8674*00
Tyre Size	VF 650/65R42 NRO (SB)
Rec Rim	DW23B
Alternate Rim	DW21B
NRO	DW20B
PR & LI/SI	174 D
Section Width (mm)	650
Overall Diameter (mm)	1913
Static Load Radius (mm)	882
Rolling Circumference (mm)	5745
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	3720	4330	4960	5410	6610	7370
25	3480	4060	4650	5070	6190	6900
30	3450	4020	4600	5020	6130	6830
40	3380	3940	4510	4920	6010	6700
50	3380	3940	4510	4920	6010	6700
65	3380	3940	4510	4920	6010	6700
70	3100	3610	4140	4510	5510	6150