

## VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

### Salient Features & Benefits

### VF Drive Radial 2000, specially designed Ultra Modern Tractor.

#### Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

#### Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

#### Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

#### Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

#### Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

#### Longer Tyre Life

- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

#### NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



## Machineries



**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*8673*00
Tyre Size	VF 710/60R42 NRO (SB)
Rec Rim	DW25B
Alternate Rim	DW24B,DW27B
NRO	DW23B
PR & LI/SI	176 D
Section Width (mm)	708
Overall Diameter (mm)	1919
Static Load Radius (mm)	885
Rolling Circumference (mm)	5763
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	3850	4490	5140	5780	7060	7810
25	3610	4200	4810	5410	6610	7310
30	3570	4160	4760	5360	6550	7240
40	3500	4080	4670	5250	6420	7100
50	3500	4080	4670	5250	6420	7100
65	3500	4080	4670	5250	6420	7100
70	3210	3740	4280	4820	5890	6510