

XLR 880 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

Xtra Large Radial 880 tyres, specially designed for the latest, most modern and most powerful tractor.

Outstanding Traction

- Optimized tread design with a deep centre tread.
- Less slippage & Maximum performance in field and on road operations.

Reduced Soil Compaction

- Wider and Longer Footprint with a larger inner volume.
- Reduce Soil stress, compaction, resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher load-carrying capacity

- Optimized radial structure.
- Can carry very high loads reaching up to 65 km/h (40 mph).

Prevent lug shuffling in operation

- First in the industry with dual Mud Breakers.
- Provides Excellent self-cleaning properties.

Handling & Comfortable ride at high speed

- Better Lug Overlap.
- Outstanding road performances in terms of comfort and safety at high speeds.



Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	710/70R42 (HD)
Rec Rim	DW23B
Alternate Rim	DW25B
PR & LI/SI	173D
Section Width (mm)	716
Overall Diameter (mm)	2061
Static Load Radius (mm)	944
Rolling Circumference (mm)	6164
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.2	1.6	2	2.4
Static	8140	10470	12790	14030	14950

Mixed Application

km/h / bar	0.8	1.2	1.6	2	2.4
10	5310	6830	8340	9150	9750
25	4190	5390	6590	7230	7700
30	4070	5230	6390	7020	7480
40	3880	4980	6090	6680	7120
50	3720	4780	5840	6410	6830
65	3540	4550	5560	6100	6500