

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Tractor

Harvester

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	VF 710/70R42 NRO (SB)
Rec Rim	DW25B
Alternate Rim	DW23B,DW24B
NRO	DW23B
PR & LI/SI	185 D
Section Width (mm)	705
Overall Diameter (mm)	2061
Static Load Radius (mm)	944
Rolling Circumference (mm)	6189
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4
10	4660	5450	6230	7000	8560	9390	10180
25	4370	5100	5830	6550	8010	8800	9530
30	4320	5050	5770	6490	7940	8710	9440
40	4240	4950	5660	6360	7780	8540	9250
50	4240	4950	5660	6360	7780	8540	9250
65	4240	4950	5660	6360	7780	8540	9250
70	3890	4540	5190	5830	7140	7830	8490