

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/21*10892*00
Tyre Size	VF 710/75R42 NRO (SB)
Rec Rim	DW24B
Alternate Rim	DW23B,DW25B
NRO	DW23B
PR & LI/SI	184 D
Section Width (mm)	720
Overall Diameter (mm)	2160
Static Load Radius (mm)	984
Rolling Circumference (mm)	6486
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	4960	5790	6610	7440	9100	9900
25	4650	5420	6190	6960	8520	9270
30	4600	5370	6130	6900	8440	9180
40	4510	5260	6010	6760	8270	9000
50	4510	5260	6010	6760	8270	9000
65	4510	5260	6010	6760	8270	9000