

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	VF 900/50R42 NRO (SB)
Rec Rim	DW30B
Alternate Rim	-
NRO	DW28B
PR & LI/SI	180 D/ 177 E
Section Width (mm)	881
Overall Diameter (mm)	1967
Static Load Radius (mm)	905
Rolling Circumference (mm)	5907
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6
10	4730	5510	6300	7100	8800
25	4430	5160	5900	6640	8240
30	4390	5110	5840	6580	8160
40	4300	5010	5730	6450	8000
50	4300	5010	5730	6450	8000
65	4300	5010	5730	6450	8000
70	3940	4600	5260	5920	7300